Owner / Applicant Information		
Karyn Bostic		
Schindler Elevator Corp		
1530 TIMBERWOLF DR		
HOLLAND OH 43528		
Phon∈ 4198615908		
Email KARYN.BOSTIC@SCHINDLER.COM		
Email Wiktiv.bostioe Sofiiwbeek.oow		
Project Information		
1700 Magnavox Way		
1700 Magnavox Way		
1700 Magnavox Way		
Fort Wayne 46809		
County ALLEN		
Project Type New Y Addition Alteration Existing Change of Occupancy		
Project Status F F=Filed U or Null=Unfiled		
IDHS Issued Correction order? No Has Violation been Issued? No		
<u>Violation Issued by:</u> NA		
Local Building Official		
Phone: 2604494671 Email: john.caywood@co.allen.in.us		
Local Fire Official		
Phone: 2604494671 Email: eric.lahey@cityoffortwayne.org		

Variance Details

Code Name: ASME A17.1 2007

2.20.1,2.20.4,2.20.9 1 and 2.1

Schindler Elevator will utilize 6mm steel wire governor rope instead of the required minimum dia. of 9.5mm per Section 2.18.5., this cable meets ASME code Section 2.18.5.1 Factor of Safety. Conditions:

DEMONSTRATION THAT PUBLIC HEALTH, SAFETY, AND WELFARE ARE PROTECTED: 1=Non-compliance with the rule will not be adverse to the public health, safety or w 1 2= Applicant will undertake alternative actions in lieu of compliance with the rule to ensure that granting of the variance will not be adverse to public health, safety, or welfare. Explain why alternative actions would be adequate (be specific). 1) The elastomeric coated elevator suspension is designed to conform with ASME A 17. 1, Facts: 2010 and ASME A 17.6, 2010 and is ANSI AECO certified to ASME A 17.7, 2007. The A 17.7 ANSI AECO certification was submitted to Mr. John Haines on December 6, 2010. The suspension members and its terminations have a factor of safety equivalent to the factor of safety for the same suspension capacity as specified in ASME A 17.1, 2007. 2) The 6mm steel governor rope is designed to conform with ASME A 17.1, 2010 and ASME A 17.6-2010 and is ANSI AECO certified to ASME A17.7, 2007. The A17.7 ANSI AECO certification was submitted to Mr. John Haines on December 6, 2010. The rope has a factor of safety 29 which is approximately six times the minimum factor of safety of 5 for 9.5mm governor ropes in ASME A 17.1 .. 2007. *Schindler will provide the tooling and training for State inspectors to conduct the required inspections of equipment.

DEMONSTRATION OF UNDUE HARDSHIP OR HISTORICALLY SIGNIFICANT STRUCTURE:

	Imposition of the rule would result in an undue hardship (unusual difficulty) because of physical limitations of the construction site or its utility services.
	Imposition of the rule would result in an undue hardship (unusual difficulty) because of major operational problems in the use of the building or structure.
Υ	Imposition of the rule would result in an undue hardship (unusual difficulty) because of excessive costs of additional or altered construction elements.
	Imposition of the rule would prevent the preservation of an architecturally or a historically significant part of the building or structure
Facts:	Excessive cost for construction for equivalent equipment using steel ropes suspension and governor ropes covered under A17 1-2007 1) The elastomeric coated elevator suspension, terminations, and its monitoring is designed to conform with ASME A 17. 1, 2010 and ASME A 17.6, 2010 and is ANSI AECO certified to ASME A 17.7, 2007. The A 17.7 ANSI AECO certification was submitted to Mr. John Haines on December 6, 2010 and is updated in this submission. The suspension members and its terminations have a factor of safety equivalent to the factor of safety for the same suspension capacity as specified in ASME A 17.1, 2007. 2) The 6mm steel governor rope is designed to conform with ASME A 17.1, 2010 and ASME A 17.6-2010 and is ANSI AECO certified to ASME A17.7, 2007. The A17.7 ANSI AECO certification was submitted to Mr. John Haines on December 6, 2010 and updated in this submission.