susan ruhana schindler elevator corp 2325 EXECUTIVE DR INDIANAPOLIS IN 46241
2325 EXECUTIVE DR
INDIANAPOLIS IN 46241
INDIANAI OLIS III 10211
Discuss 247/4/7004
Phon∈ 3176167981
Email SUSAN.RUHANA@SCHINDLER.COM
Draiget Information
Project Information
WATERMARK AT FISHERS
9700 E 116TH ST
FISHERS 46037
County HAMILTON
Project Type New Y Addition Alteration Existing Change of Occupancy
Project Status U F=Filed U or Null=Unfiled
IDHS Issued Correction order? No Has Violation been Issued? No
<u>Violation Issued by:</u> NA
Local Building Official
Phone: 3175953200 Email: Chuck.kiphart@hamiltoncounty.in.gov
Local Fire Official
Phone: 3175953200 Email: hootenb@fishers.in.us

Variance Details

Other Code (Not in the list provided) Code Name:

ANSI ASME A 17.1-2007, 2.20.1,

Schindler Elevator will utilize 6mm steel wire governor rope instead of the required minimum dia. of 9.5mm per Section 2.18.5., this cable meets ASME code Section 2.18.5.1 Factor of Safety. Conditions:

DEMONSTRATION THAT PUBLIC HEALTH, SAFETY, AND WELFARE ARE PROTECTED: 1=Non-compliance with the rule will not be adverse to the public health, safety or w 1 2= Applicant will undertake alternative actions in lieu of compliance with the rule to ensure that granting of the variance will not be adverse to public health, safety, or welfare. Explain why alternative actions would be adequate (be specific). 1) The elastomeric coated elevator suspension is designed to conform with ASME A 17. 1, Facts: 2010 and ASME A 17.6, 2010 and is ANSI AECO certified to ASME A 17.7, 2007. The A 17.7 ANSI AECO certification was submitted to Mr. John Haines on December 6, 2010. The suspension members and its terminations have a factor of safety equivalent to the factor of safety for the same suspension capacity as specified in ASME A 17.1, 2007. 2) The 6mm steel governor rope is designed to conform with ASME A 17.1, 2010 and ASME A 17.6-2010 and is ANSI AECO certified to ASME A17.7, 2007. The A17.7 ANSI AECO certification was submitted to Mr. John Haines on December 6, 2010. The rope has a factor of safety 29 which is approximately six times the minimum factor of safety of 5 for 9.5mm governor ropes in ASME A 17.1 .. 2007. Schindler will provide the tooling and training for State inspectors to conduct the required inspections of equipment. DEMONSTRATION OF UNDUE HARDSHIP OR HISTORICALLY SIGNIFICANT STRUCTURE: Imposition of the rule would result in an undue hardship (unusual difficulty) because of physical limitations of the construction site or its utility services. Imposition of the rule would result in an undue hardship (unusual difficulty) because of major operational problems in the use of the building or structure. Imposition of the rule would result in an undue hardship (unusual difficulty) because of excessive costs of additional or altered construction elements. Imposition of the rule would prevent the preservation of an architecturally or a historically significant part of the building or structure Excessive cost for construction for equivalent equipment using steel ropes suspension and Facts: governor ropes covered under A17 1-2007 1) The elastomeric coated elevator suspension, terminations, and its monitoring is designed to conform with ASME A 17. 1, 2010 and ASME A 17.6, 2010 and is ANSI AECO certified to ASME A 17.7, 2007. The A 17.7 ANSI AECO certification was submitted to Mr. John Haines on December 6, 2010 and is updated in this submission. The suspension members and its

terminations have a factor of safety equivalent to the factor of safety for the same suspension

2) The 6mm steel governor rope is designed to conform with ASME A 17.1, 2010 and ASME A 17.6-2010 and is ANSI AECO certified to ASME A17.7, 2007. The A17.7 ANSI AECO certification was submitted to Mr. John Haines on December 6, 2010 and updated in this submission.

capacity as specified in ASME A 17.1, 2007.