

Owner / Applicant Information

Clayton Trueblood
Holladay Construction
6370 AMERIPLEX DRIVE
STE 110
PORTAGE IN 46368
Phone 2197621376
Email JACQUELYN.ESPINOZA@SCHINDLER.COM

Submitter Information

Jacquelyn Espinoza
Schindler Elevator
853 N Church Ct

Elmhurst IN

Phone 6304787139
Email jacquelyn.espinoza@schindler.com

Project Information

The Illiana Mixed Use
1200 119th St

Whiting IL 46394

County LAKE

Project Type New ☒ Y Addition ☐ Alteration ☐ Existing ☐ Change of Occupancy ☐

Project Status ☒ U F=Filed U or Null=Unfiled

IDHS Issued Correction order? ☒ No Has Violation been Issued? ☒ No

Violation Issued by: NA

Local Building Official

Phone: Email:

Local Fire Official

Phone: Email:

Variance Details

Code Name: ASME A17.1 2007

2.20.1,2.20.4,2.20.9 1, 2.18.5

Conditions:	<p>1) The elastomeric coated elevator suspension is designed to conform with ASME A 17. 1, 2010 and ASME A 17.6, 2010 and is ANSI AECO certified to ASME A 17.7, 2007. The A 17.7 ANSI AECO certification was submitted to Mr. John Haines on December 6, 2010.</p> <p>The suspension members and its terminations have a factor of safety equivalent to the factor of safety for the same suspension capacity as specified in ASME A 17.1, 2007.</p> <p>2) The 6mm steel governor rope is designed to conform with ASME A 17.1, 2010 and ASME A 17.6-2010 and is ANSI AECO certified to ASME A17.7, 2007. The A17.7 ANSI AECO certification was submitted to Mr. John Haines on December 6, 2010. The rope has a factor of safety 29 which is approximately six times the minimum factor of safety of 5 for 9.5mm governor ropes in ASME A 17.1 .. 2007.</p> <p>*Schindler will provide the tooling and training for State inspectors to conduct the required inspections of equipment.</p>
-------------	--

DEMONSTRATION THAT PUBLIC HEALTH, SAFETY, AND WELFARE ARE PROTECTED:

1=Non-compliance with the rule will not be adverse to the public health, safety or w

1	2= Applicant will undertake alternative actions in lieu of compliance with the rule to ensure that granting of the variance will not be adverse to public health, safety, or welfare. Explain why alternative actions would be adequate (be specific).
---	--

Facts:	<p>Excessive cost for construction for equivalent equipment using steel ropes suspension and governor ropes covered under A17 1-2007</p> <p>1) The elastomeric coated elevator suspension, terminations, and its monitoring is designed to conform with ASME A 17. 1, 2010 and ASME A 17.6, 2010 and is ANSI AECO certified to ASME A 17.7, 2007. The A 17.7 ANSI AECO certification was submitted to Mr. John Haines on December 6, 2010 and is updated in this submission. The suspension members and its terminations have a factor of safety equivalent to the factor of safety for the same suspension capacity as specified in ASME A 17.1, 2007.</p> <p>2) The 6mm steel governor rope is designed to conform with ASME A 17.1, 2010 and ASME A 17.6-2010 and is ANSI AECO certified to ASME A17.7, 2007. The A17.7 ANSI AECO certification was submitted to Mr. John Haines on December 6, 2010 and updated in this submission.</p>
--------	---

DEMONSTRATION OF UNDUE HARDSHIP OR HISTORICALLY SIGNIFICANT STRUCTURE:

<input type="checkbox"/>	Imposition of the rule would result in an undue hardship (unusual difficulty) because of physical limitations of the construction site or its utility services.
<input type="checkbox"/>	Imposition of the rule would result in an undue hardship (unusual difficulty) because of major operational problems in the use of the building or structure.
<input checked="" type="checkbox"/>	Imposition of the rule would result in an undue hardship (unusual difficulty) because of excessive costs of additional or altered construction elements.
<input type="checkbox"/>	Imposition of the rule would prevent the preservation of an



imposition of the rule would prevent the preservation of an architecturally or a historically significant part of the building or structure

Facts:

Excessive cost for construction for equivalent equipment using steel ropes suspension and governor ropes covered under A17.1-2007

- 1) The elastomeric coated elevator suspension, terminations, and its monitoring is designed to conform with ASME A 17.1, 2010 and ASME A 17.6, 2010 and is ANSI AECO certified to ASME A 17.7, 2007. The A 17.7 ANSI AECO certification was submitted to Mr. John Haines on December 6, 2010 and is updated in this submission. The suspension members and its terminations have a factor of safety equivalent to the factor of safety for the same suspension capacity as specified in ASME A 17.1, 2007.
- 2) The 6mm steel governor rope is designed to conform with ASME A 17.1, 2010 and ASME A 17.6-2010 and is ANSI AECO certified to ASME A17.7, 2007. The A17.7 ANSI AECO certification was submitted to Mr. John Haines on December 6, 2010 and updated in this submission.